

Model Number 353B18		ACCELEROMETER, ICP®		Revision N ECN #: 35369	
Performance		ENGLISH	SI	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)	
Sensitivity (±10 %)	10 mV/g	1.02 mV/(m/s²)		A - Adhesive Mount	
Measurement Range	±500 g pk	±4905 m/s² pk		Supplied Accessory: Model 080A90 Quick bond Gel (for use with accelerometer adhesive mtg bases to fill gaps on rough surfaces) replaces Model 080A15	
Frequency Range (±5 %)	1 to 10000 Hz	1 to 10000 Hz		B - Low bias electronics	
Frequency Range (±10 %)	0.7 to 18000 Hz	0.7 to 18000 Hz		Output Bias Voltage	4.5 to 7.5 VDC
Frequency Range (±3 dB)	0.35 to 30000 Hz	0.35 to 30000 Hz		Excitation Voltage	12 to 30 VDC
Resonant Frequency	≥70 kHz	≥70 kHz		Constant Current Excitation	1 to 20 mA
Broadband Resolution (1 to 10000 Hz)	0.005 g rms	0.05 m/s² rms	[1]	Measurement Range	±300 g pk
Non-Linearity	≤1 %	≤1 %	[2]		±2943 m/s² pk
Transverse Sensitivity	≤5 %	≤5 %	[3]	J - Ground Isolated	
Environmental				Frequency Range (±5 %)	1 to 8000 Hz
Overload Limit (Shock)	±10000 g pk	±98100 m/s² pk		Frequency Range (±10 %)	0.7 to 15000 Hz
Temperature Range (Operating)	-65 to +250 °F	-54 to +121 °C		Resonant Frequency	≥56 kHz
Temperature Response	See Graph	See Graph	[1]	Electrical Isolation (Base)	≥10⁸ ohm
Base Strain Sensitivity	≤0.003 g/με	≤0.03 (m/s²)/με	[1]	Size (Hex x Height)	3/8 in x 0.82 in
Electrical				Weight	0.10 oz
Excitation Voltage	18 to 30 VDC	18 to 30 VDC			3.0 gm
Constant Current Excitation	2 to 20 mA	2 to 20 mA		M - Metric Mount	
Output Impedance	≤100 ohm	≤100 ohm		Mounting Thread	M3 x 0.50 Male
Output Bias Voltage	8 to 12 VDC	8 to 12 VDC			(M3 x 0.50 Male)
Discharge Time Constant	0.5 to 2.0 sec	0.5 to 2.0 sec		Supplied Accessory: Model M080A15 Metric adhesive base, 0.31" hex x 0.125" thk, M3 x 0.50 thd, aluminum with insulating hardcoat finish replaces Model 080A15	
Spectral Noise (1 Hz)	2800 μg/√Hz	27468 (μm/sec²)/√Hz	[1]	Q - Extended discharge time constant	
Spectral Noise (10 Hz)	700 μg/√Hz	6867 (μm/sec²)/√Hz	[1]	Frequency Range (±5 %)	0.15 to 10000 Hz
Spectral Noise (100 Hz)	180 μg/√Hz	1766 (μm/sec²)/√Hz	[1]	Frequency Range (±10 %)	0.1 to 18000 Hz
Spectral Noise (1 kHz)	64 μg/√Hz	628 (μm/sec²)/√Hz	[1]	Discharge Time Constant	>5 sec
Physical				Settling Time (within 10% of bias)	<45 sec
Sensing Element	Quartz	Quartz		Supplied Accessory: Model ACS-97 Single axis, low frequency phase and amplitude response cal from 1 to 10 Hz	<45 sec
Sensing Geometry	Shear	Shear		W - Water Resistant Cable	
Housing Material	Titanium	Titanium		Electrical Connector	Sealed Integral Cable
Sealing	Welded Hermetic	Welded Hermetic			Sealed Integral Cable
Size (Hex x Height)	9/32 in x 0.74 in	9/32 in x 18.8 mm		Electrical Connection Position	Top
Weight	0.06 oz	1.8 gm	[1]		Top
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack		Notes	
Electrical Connection Position	Top	Top		[1] Typical.	
Mounting Thread	5-40 Male	5-40 Male		[2] Zero-based, least-squares, straight line method.	
Mounting Torque	8 to 12 in-lb	90 to 135 N-cm		[3] Transverse sensitivity is typically ≤ 3%.	
				[4] See PCB Declaration of Conformance PS023 for details.	
				Supplied Accessories	
				080A109 Petro Wax (1)	
				080A15 Adhesive Mounting Base (1)	
				ACS-1 NIST traceable frequency response (10 Hz to upper 5% point). (1)	

